

Learning, Assisting and Providing Positive Solutions
And we're just getting started. Call us today at 800-822-2565 to see how we can help you.

COMPRESSION FIT PIPE TO MANHOLE CONNECTORS

	SIZE/RANGE	Omni-directional Deflection	APPLICATIONS
A•LOK X•CEL	4.25"-102.00"	10 Degrees	<ul style="list-style-type: none"> • Performance watertight connector for sanitary, storm, and light industrial demand. • Watertight connector for storm and light industrial demand. • Watertight connector for cored or cast openings in new or insitu type construction. • Flexible watertight connector for sanitary or storm.
A•LOK STM	8.50"-102.00"	10 Degrees	
INSERTA•LOK	4.25"-16.00"	7 Degrees	
A•LOK PREMIUM	8.50"-102.00"	10 Degrees	

BOOT TYPE PIPE TO MANHOLE CONNECTORS

Z•LOK	1.25"-21.25"	25 Degrees	<ul style="list-style-type: none"> • Cast-in place watertight connector for sanitary, storm, and light industrial demand. • Expanded-In-Place watertight connector for watertight, storm, and sanitary demands. • Cast in place connector for storm or sanitary systems. using smooth wall or corrugated pipe. • Cast in place watertight connector for sanitary, storm and light industrial demand with attached take-down clamp.
G-3	3.50"-13.50"	15 Degrees	
Z-LOK STM/Smooth Wall	14.00"-102.00"	15 Degrees/Minimum	
Z-LOK STM/Corrugated	14.50"-41.50"	15 Degrees/Minimum	
QUIK-LOK	4.00"-13.00"	25 Degrees	

SEPTIC TANK CONNECTORS – BOOT STYLE & COMPRESSION

A•LOK SEPTIC SEAL	1.5"-4.50"	7 Degrees	<ul style="list-style-type: none"> • Performance watertight connector for septic structures. • Performance watertight connector for septic structures with attached take-down clamp.
QUIK-LOK SEPTIC SEAL	4.0"-4.50"	10 Degrees	

GROUTED IN CONNECTIONS

WATER-STOP	4.25"-120.00"	<ul style="list-style-type: none"> • Designed for NEW or EXISTING structures to seal cold joint pipe penetrations, creating a <u>watertight</u> and <u>soil-tight</u> seal between pipe and connector. Provides a surface for concrete and grout to adhere. For smooth wall or corrugated pipe.
------------	---------------	--

CORROSION RESISTANT LINERS

	SIZE/RANGE	Minimum Thickness	
DURA PLATE 100	48.00"-144.00"	65 Mils.	<ul style="list-style-type: none"> • Interior protection for round concrete structures from hydrogen sulfide and other acidic conditions in wastewater, and light industrial structures.

ENTRY SEALS

	SIZE/RANGE	Height Adjustment Capabilities	
WATER•LOK	24", 27", 30"	0.00"-14.00"	<ul style="list-style-type: none"> • Telescoping watertight seals for flexible grade adjustment in wastewater, storm, and light industrial structures.

SPACERS & REINFORCEMENT ACCESSORIES

Non-Corrosive plastic Pyramid-lok spacers and metal spacers for round, arch and elliptical pipe, manholes, box sections, catch basins, septic tanks and cast in place products. Hoop Supports to hold single wire reinforcement in place.

KEY•LOK LIFT SYSTEM

Certified manhole lifting system for wall thickness up to 6.00" and weights up to 6,500 lbs.

Includes: KEY•LOK Lift Inserts, Lift Insert Holders, Lift Pins & Lift Bars.

INVERT CHANNELING EQUIPMENT

	SIZE RANGE	Increments	
A•LOK PRIMARY SYSTEM	8", 10", 12"	7 Degrees	<ul style="list-style-type: none"> • Monolithic pour casting equipment for wastewater and storm structures. • Secondary pour casting equipment for wastewater and storm structures.
TRU-CONTOUR	4.00"-48.00"	Available in	
SECONDARY SYSTEM		2 Degree increments	

ADDITIONAL A•LOK PRODUCTS

HOLE FORMERS - METAL & FIBERGLASS
 MANDRELS
 VERTITE ELASTOMERIC SEALS FOR PIPES
 OR MANHOLES

AVANTI GROUT REPAIR SEALANTS
 BUTYL-LOK SEALANTS
 GRANDSLAM LUBE
 BOLT SLOT ANCHORS

MAGNETIC: STEP INSERT HOLDERS,
 MANDRELS, HOLE FORMERS
 CAST-IN-PLACE FIELD SLEEVES

Copyright 2009 © A•LOK Products, Inc.

Visit our website - www.a-lok.com
 800-822-2565 • 215-547-3366 • FAX 215-547-5260
 P.O. Box 1647 • Tullytown, PA 19007 • info@a-lok.com