

# MAXIMUM PARALLEL PIPE LAYOUT FOR STANDARD Z•LOK MANDRELS

		MANHOLE DIAMETER							
CONNECTOR	PIPE	48"	60"	72"	84"	96"	108"	120"	144"
C107-01	PVC	27.0	30.5	33.0	36.0	38.5	41.5	44.0	49.5
C107-02	PVC	23.5	27.5	31.0	33.5	36.5	39.0	42.5	47.5
C107-03	PVC	23.5	27.5	31.0	33.5	36.5	39.0	42.5	47.5
C107-04	PVC	23.5	27.0	30.5	34.5	37.5	40.5	43.5	46.5
	D.I.	21.5	25.0	28.5	31.5	34.5	37.0	39.5	45.0
	VC	19.5	23.5	26.0	28.5	30.5	34.0	37.5	43.0
C107-06	PVC	21.5	25.0	27.0	32.5	36.0	39.5	43.0	46.5
	D.I.	19.5	23.5	25.0	30.5	34.0	37.5	39.5	45.0
	VC	18.0	21.5	23.5	28.5	32.5	36.0	37.5	43.0
F208-08	PVC	18.0	19.5	21.5	23.5	25.0	27.0	30.5	36.0
	D.I.	14.5	16.0	18.0	19.5	21.5	23.5	27.0	32.5
C107-08	PVC	23.5	25.0	27.0	30.5	34.0	37.5	41.5	46.5
	D.I.	21.5	23.5	25.0	28.5	32.5	36.0	39.5	45.0
	VC	19.5	21.5	23.5	27.0	30.5	34.0	37.5	43.0
C107-10	PVC	21.5	23.5	25.0	28.5	34.0	37.5	43.0	46.5
	D.I.	19.5	21.5	23.5	27.0	32.5	36.0	41.5	45.0
	VC	18.0	19.5	21.5	25.0	30.5	34.0	39.5	43.0
C107-12	PVC	19.5	23.5	28.5	34.0	39.5	45.0	46.5	48.5
	D.I.	19.5	21.5	27.0	32.5	36.0	41.5	43.0	45.0
	VC	NA	20.5	25.0	28.5	32.5	34.0	39.5	41.5
C107-15	PVC	NA	21.5	24.5	27.0	32.5	36.0	37.5	45.0
C107-16	D.I.	NA	NA	27.0	30.5	34.0	37.5	41.5	45.0
	VC	NA	NA	25.0	27.0	30.5	34.0	37.5	41.5
C107-18	PVC	NA	NA	NA	23.5	27.0	28.5	32.5	36.0
	D.I.	NA	NA	NA	21.5	25.0	27.0	30.5	34.0

**NOTE:**  
Skived mandrels are available where greater center to center are required.

